

Instructions for MAV 500 Top Box Light Pro LED Panel

- 1) Remove top box display glass to expose fluorescent, large white reflector tray, ballast and ballast wiring, Power down game.
- 2) Remove Light Pro panel from box and connect the Suzo-Happ power adaptor cable #70-0214-00 to the cable end of the #70-36590-00 Suzo-Happ Light Pro LED panel. Remove protective plastic covering to each side of LED panel.
- 3) Take the dual sided foam tape provided in the box to make four 2” pieces. Attach a 2” piece of foam tape to the rear corners of the light panel. The panel includes approximately 30” of two sided foam tape for additional installations.
- 4) Disconnect to two-pin 24VDC input connector that connects to the ballast located in the top box. Connect the two-pin connector side of the 70-2140-00 to the two-pin connector previously removed from the top box ballast.
- 5) Turn on game to test proper operation of panel. At this point you will see that the LED light panel has a brighter side. Your two sided tape strips should be mounted on the dimmer side of the LED panel.
- 6) Remove the protective cover strips from the foam adhesive tape strips.
- 7) Remove fluorescent lamp.
- 8) Position LED panel and attach to the upper portion of the white reflective light tray.
- 9) Re-install top box glass and frame

Thank-You for purchasing the Suzo-Happ Light Pro LED Panel.

Check out our full line of LED panels @ suzohapp.com or contact your sales representative.