
Heavy Duty Grade Vinyl Plugs & Connectors

2-Pole, 3-Wire Grounding 15A, 125V/AC 20A, 125V/AC



Features

- · Solid brass plug blades are firmly embedded in body
- · Vinyl plugs and connectors resist chemical attack and are less brittle in extremely low temperatures
- · Vinyl angle plugs have eight possible positions for maximum convenience
- · Terminal screws backed out and ready for wiring
- · Terminals in individual chambers to positively insulate conductors
- · Terminal screw clamps are designed to contain wire and prevent binding
- · Combination Slot/Phillips head mounting and terminal screws for installation flexibility (Slot/ Robertson screws in Canada where available)



4867ANW



4229

Vinyl Plugs & Connectors							
Ra	ating V/AC	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	4
15	125	NEMA 5-15, Straight Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4867	□ 4887	•
		NEMA 5-15, Angled Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4867AN		•
		NEMA 5-15, Angled Body	0.25-0.66" (6.4-16.6mm)	W	□ 4867ANW		•
20	125	NEMA 5-20, Straight Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4409	□ 4228	•

Listed to UL498, file no. E15012; CSA

certified to C22.2, no. 42; NOM certified except 4228

Vinyl Plugs & Connectors								
R A	ating V/AC	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	\P	
	_	NEMA 5-20, Angled Body	0.25-0.66" (6.4-16.6mm)	Y	□ 4409AN		•	

Listed to UL498, file no. E15012; NOM certified except 4228

Vinyl Plugs & Connectors							
Ra A	ating V/AC	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	\P
15	250	NEMA 6-15, Straight Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4866	□ 4227	•
		NEMA 6-15, Angled Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4866AN		•
20	250	NEMA 6-20, Straight Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4509	□ 4229	•
		NEMA 6-20, Angled Body	0.25-0.66" (6.4-16.6mm)	Υ	□ 4509AN		•
Liste	Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 4227 & 4229						

Color Ordering Information:

Y (Yellow), W (White)



Dimensional Information: B-70 Specification Information: Specifications and availability are subject to change without notice.

